

PROFESSIONAL

KA 50 BLUE-MAG · SENSOR · TWIN-RAIL SLIDE

EUROPE-VERSION

230 VOLTS

USA-VERSION

110 VOLTS

UK-VERSION

110 VOLTS

20 8023 010


20 8023 020

20 8023 030

Core drilling

 Ø 5/32 to 1-31/32"
 12-50 mm

302-429, 448-462

Twist drilling

 Ø 3/16 to 29/32"
 3-23 mm

568

Countersinking

 Ø 3/8 to 1-37/64"
 10-40 mm

610-645

Accessories


463-465, 470

Speed full load


Gear stages

1 = 250 rpm

2 = 450 rpm

 The specified maximum diameter / cutting depths of the magnetic hole cutting machines, can only be guaranteed with **original** Karnasch drilling tools.

* The machines are supplied as standard with a **2" (55 mm) cutting depth** holder. For **cutting depth up to 4" (110 mm)** please use our extra long holders see pages 464/465, or see our 2-part pins (explanation see page 310) for cutters from 45/64" (18 mm). For cutting depth more than 4" (110 mm) please ask us.

Special Characteristics

Sensor

Thanks to the Heavy Duty Twin Rail Slide System, **4" (110 mm)** cutting depth is easily possible. [Description on page 1158].



Motor Power Watts

1150

Tool holder

 Morse taper 2 with Weldon 3/4"
 (19 mm)

Coolant supply

Internal, automatically

Stroke

6-5/8" | 170 mm

Voltage

110 Volts / 230 Volts

Magnetic adhesion

2755 lb | 1250 kg

Magnetic foot

 3-5/16 x
 7-1/16"
 (85 x 180 mm)

Fixed

Weight

28.00 lb
13.00 kg

Movie


Bestseller

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11