

PROFESSIONAL

KA 40 BLUE-MAG · SENSOR · TWIN-RAIL SLIDE

EUROPE-VERSION

230 VOLTS

USA-VERSION

110 VOLTS

UK-VERSION

110 VOLTS

20 8021 010


20 8021 020

20 8021 030

Core drilling

 Ø 5/32 to 1-37/64"
 12-40 mm

302-429, 448-462

Twist drilling

 Ø 3/16 to 45/64"
 3-18 mm

568

Countersinking

 Ø 3/8 to 1-3/16"
 10-30 mm

610-645

Accessories


463-465, 470

Speed full load


Gear stages

1 = 450 rpm

 The specified maximum diameter / cutting depths of the magnetic hole cutting machines, can only be guaranteed with **original** Karnasch drilling tools.

 * The machines are supplied as standard with **2" (55 mm) cutting depth holder**. Please use our 2-part pins (explanation see page 310) for cutters from 45/64" [18 mm] if you need **cutting depth up to 4" (110 mm)**.

Special Characteristics


Sensor

 Thanks to the Heavy Duty Twin Rail Slide System, **4" (110 mm) cutting depth** is easily possible. [Description on page 1158].


Motor Power Watts

1100

Tool holder

Directly Weldon 3/4" (19 mm)

Coolant supply

Internal, automatically

Stroke

6-5/8" | 170 mm

Voltage

110 Volts / 230 Volts

Magnetic adhesion

2425 lb | 1100 kg

Magnetic foot

 3-5/16 x
 6-11/16"
 (85 x 170 mm)

Fixed

Weight

25.00 lb
11.50 kg

Movie



Bestseller