

KATV 140 BLUE-MAG · SENSOR · TWIN-RAIL SLIDE

SPECIALIST

EUROPE-VERSION

230 VOLTS

USA-VERSION

110 VOLTS

UK-VERSION

110 VOLTS

20 8032 010

20 8032 020

20 8032 030


Core drilling



Ø 15/32 to 5-33/64"
12-140 mm

302-429, 448-462

Twist drilling



Ø 3/16 to 1-31/32"
3-50 mm

568

Countersinking



Ø 3/8 to 3-5/32"
10-80 mm

610-645


Tapping



Ø 15/64 to 1-47/64"
6-44 mm

569

Accessories



463-465, 470

Speed full load

Gear stages



- 1 = 30-80 rpm
- 2 = 50-120 rpm
- 3 = 130-350 rpm
- 4 = 210-550 rpm

* The machines are supplied as standard with a 2" (55 mm) cutting depth holder. For cutting depth up to 4" (110 mm) please use our extra long holders see pages 464/465, or see our 2-part pins (explanation see page 310) for cutters from 45/64" (18 mm). For cutting depth more than 4" (110 mm) please ask us.



Special Characteristics



Right/left running



Full wave electronic



Thermal/overheat protection



Mechanical clutch



Sensor

Thanks to the Heavy Duty Twin Rail Slide System, 9-7/16" (240 mm) cutting depth is easily possible. (Description on page 1158).

Motor Power Watts

2300

Accessories in machine

Adapter weldon 1-1/4" (32 mm) to 3/4" (19 mm)
For annular cutter Ø 5/32 to 2-23/64" (12-60 mm)
Morse taper 4 with weldon 1-1/4" (32 mm)
For annular cutter Ø 2-13/32 to 5-33/64" (61-140 mm)

Coolant supply

Internal, automatically

Stroke

12" | 320 mm

Voltage

110 Volts / 230 Volts

Magnetic adhesion

5897 lb | 2675 kg

Magnetic foot

4-11/16" x 9-7/16" (120 x 240 mm)

Fixed

Weight

73.00 lb
35.00 kg

Movie



Bestseller

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11

Index