

KAS 50 BLUE-MAG · SENSOR · TWIN-RAIL SLIDE

PROFESSIONAL

EUROPE-VERSION

230 VOLTS

USA-VERSION

110 VOLTS

UK-VERSION

110 VOLTS

20 8024 010

20 8024 020

20 8024 030


Core drilling



Ø 5/32 to 1-31/32"
12-50 mm

302-429, 448-462

Twist drilling



Ø 3/16 to 29/32"
3-23 mm

568

Countersinking



Ø 3/8 to 1-37/64"
10-40 mm

610-645

Accessories



463-465, 470

Speed full load



Gear stages

1 = 250 rpm

2 = 450 rpm

* The machines are supplied as standard with a 2" (55 mm) cutting depth holder. For cutting depth up to 4" (110 mm) please use our extra long holders see pages 464/465, or see our 2-part pins (explanation see page 310) for cutters from 45/64" (18 mm). For cutting depth more than 4" (110 mm) please ask us.

Special Characteristics



Sensor

Thanks to the Heavy Duty Twin Rail Slide System, 4" (110 mm) cutting depth is easily possible. [Description on page 1158].



Motor Power Watts

1150

Tool holder

Morse taper 2 with Weldon 3/4" (19 mm)

Coolant supply

Internal, automatically

Stroke

6-31/32" | 180 mm

Voltage

110 Volts / 230 Volts

Magnetic adhesion

2755 lb | 1250 kg

Magnetic foot

3-5/16 x 6-11/16"
(85 x 170 mm)

Swivel rotates

360°

Weight

29.80 lb

13.50 kg

Movie



Bestseller

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11

Index