

# KA 38 BLUE-MAG · SENSOR · TWIN-RAIL SLIDE

PROFESSIONAL

EUROPE-VERSION

230 VOLTS

USA-VERSION

110 VOLTS

UK-VERSION

110 VOLTS

20 8020 010

20 8020 020

20 8020 030


Core drilling



Ø 5/32 to 1-1/2"  
12-38 mm

302-429, 448-462

Twist drilling



Ø 3/16 to 45/64"  
3-18 mm

568

Countersinking



Ø 3/8 to 1-3/16"  
10-30 mm

610-645

Accessories



463-465, 470

Speed full load



Gear stages

1 = 450 rpm

The specified maximum diameter / cutting depths of the magnetic hole cutting machines, can only be guaranteed with **original** Karnasch drilling tools.

\* The machines are supplied as standard with 2" (55 mm) cutting depth holder. Please use our 2-part pins (explanation see page 310) for cutters from 45/64" (18 mm) if you need cutting depth up to 4" (110 mm).

Special Characteristics



Sensor

Thanks to the Heavy Duty Twin Rail Slide System, 4" (110 mm) cutting depth is easily possible. (Description on page 1158).



Motor Power Watts	1100
Tool holder	Directly Weldon 3/4" (19 mm)
Coolant supply	Internal, automatically
Stroke	6-5/8"   170 mm
Voltage	110 Volts / 230 Volts
Magnetic adhesion	2425 lb   1100 kg
Magnetic foot	3-5/16 x 6-11/16" (85 x 170 mm) Fixed
Weight	23.00 lb   10.50 kg

Movie



Bestseller

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11

Index